





# m12 Overmolded With Cable

M12 Overmolded With Cable (Plastic Nut), Female, A, B & D-Coding

Description	Molded with Cable, 180°, Screw Type, Plastic
Figure	

Drawing	
---------	--

Coding	A-Coding (X=1)	B-Coding (X=2)	D-Coding (X=4)
			

Part No.	A-Coding (X=1)		B-Coding (X=2)		D-Coding (X=4)	
	Contacts	Part Number	Contacts	Part Number	Contacts	Part Number
A, B, D-Coding	3	56034X03-01-Yxx	4	56044X03-01-Yxx		
	5	56054X03-01-Yxx				
A-Coding	8	56084103-01-Yxx	12	56124103-01-Yxx		

Specifications					
Number of Contacts	3	4	5	8	12
Voltage Rating	250V	250V	60V	30V	30V
Rated Current (40°C)	4A	4A	4A	2A	1.5A
Environmental Protection	IP67				
Mechanical Life	100 mating cycles (min)				
Operating Temperature	-25°C - 85°C (Depending on Jacket Material)				
CableType					
Wire Gauge	0.34mm <sup>2</sup> (22AWG)	0.34mm <sup>2</sup> (22AWG)	0.34mm <sup>2</sup> (22AWG)	0.25mm <sup>2</sup> (24AWG)	0.14mm <sup>2</sup> (26AWG)
Jacket Material	*Y - denotes Jacket Material/Cable Type 4 - PVC (UL/CSA) / 5 - PUR (UL/CSA)				
Jacket Color	Yellow (PVC UL2517) / Black (PUR UL20549) /				
Cable O.D. Range	Max. 6.0mm				

Note : xx-denotes Cable length in Meters (m). Standard lengths available from 1M (01) to 20M (20)

About CHOGORI  
 Industrial Automation  
 To Order  
 M8 Series  
 M12 Series  
 USB Series  
 RJ45 Series  
 D-SUB Series