

## Cable gland


### Metal Cable gland

Material: Nickel-plated brass

Seal Material: NBR

Degree of protection: IP68 Temperature range: Stat: -40°C to 100°C

Dyn: -20°C to 80°C



Thread	Claping range	(AG)	(SW)	(GL)
<b>PG Thread</b>				
PG7	3-6.5	12.5	14	6
PG9	4-8	15.2	18	6.5
PG11	5-10	18.6	20	7
PG13.5	6-12	20.4	22	7.5
PG16	8-14	22.5	24	7.5
PG21	13-18	28.3	30	8
PG29	18-25	37.0	40	9.5
PG36	22-32	47.0	50	12
PG42	31-38	54.0	55	12
PG48	37-44	59.3	65	12
<b>Metric</b>				
M12X1.5	3-6.5	12	14	6
M16X1.5	4-8	16	18	6.5
M20X1.5	6-12	20	22	8
M25X1.5	9-16	25	27	8
M25X1.5	13-18	25	30	8
M32X1.5	18-25	32	40	9
M40X1.5	22-32	40	50	12
M50X1.5	31-38	50	57	12
M63X1.5	37-44	63	65	12


### Plastics Cable gland

Material: Nylon

Seal Material: NBR

Degree of protection: IP68 Temperature range: Stat: -40°C to 100°C

Dyn: -20°C to 80°C



Thread	Claping range	(AG)	(SW)	(GL)
<b>PG Thread</b>				
PG7	3-6.5	12.5	15	8
PG9	4-8	15.2	19	8
PG11	5-10	18.6	22	8
PG13.5	6-12	20.4	24	9
PG16	8-14	22.5	27	10
PG21	13-18	28.3	32	11
PG29	18-25	37.0	42	11
PG36	22-32	47.0	52	12
PG42	31-38	54.0	59	14
PG48	37-44	59.3	65	14
<b>Metric</b>				
M12X1.5	3-6.5	20	16.7	7
M16X1.5	4-8	16	19	8
M20X1.5	5-10	18	22	8
M25X1.5	6-12	20	24	9
M25X1.5	13-18	25	32	11
M32X1.5	18-25	32	42	11
M40X1.5	22-32	40	52	12
M50X1.5	31-38	50	59	15
M63X1.5	37-44	63	65	14