



1. INTERFACE PER MIL-STD-348
2. COUPLING NUT RETENTION: 15 INCH\*LBS
3. COUPLING NUT RETENTION: 60 LBS AXIAL
4. CONTACT RETENTION: 6 LBS AXIAL
5. INSULATOR RETENTION: 6 LBS AXIAL
6. DUREBILITY: TEST AFLER 100 CYCLES

MATERIAL : BODY-BRASS  
 SLEEVE-BRASS  
 CONTACT-BERYLLIUM COPPER  
 INSULATOR-TEFLON  
 SHELL-BRASS  
 C WASHER-SUS 304  
 SI RUBBER-SILICONE  
 CAP-BRASS  
 FERRULE-BRASS

FINISH : BODY-NICKEL PLATING  
 SLEEVE-NICKEL PLATING  
 SHELL-NICKEL PLATING  
 CAP-NICKEL PLATING  
 FERRULE-NICKEL PLATING  
 CONTACT-GOLD PLATING OVER NICKEL

DIMENSIONS ARE IN MILLIMETERS			
TOLERANCE			
· × ±0.5	ANGLE ±3°	SCALE 5:1	TITLE REVERSE POLARITY SMA R/A PLUG CRIMP FOR RG58u, RG58A/u, RG141A/u
· × × ±0.1		REV A-1	
· × × × ±0.05			DRAWING NO RP-SMA-1101-TGG
DRAWN		DATE 100.04.13	FILE NO
APPROVAL		DATE	