



## EURO D4-2/35 - Typ 43553 Diode

## EURO D4-2/35 - Typy 43554 Diode




4 mm<sup>2</sup>

4 mm<sup>2</sup>

Dimensioni / Dimensions  
MI Standards

Approvazioni / Approvals

Capacità di connessione / Connecting capacity



Coppia di serraggio / Max tightening torque

Tratto da spellare / Stripping length

Pz. conf. / Qty.p.pck.

75 (L) x 56 (H) x 6 (B)  
4 mm<sup>2</sup> - 1000V - 32A

UL 600V 30A SEV 800V 32A  
CSA 600V 30A RINA 800V 32A  
VDE 1000V 32A Kema Ex II 2 GD EEx e II 03ATEX2118 U  
EN 60068-2-11 Test di nebbia salina per 96 ore / Salt mist test for 96 hours  
Conduttori rigidi / Rigid conductors mm<sup>2</sup> 0,5 - 6  
Conduttori flessibili / Flexible conductors mm<sup>2</sup> 0,5 - 4  
AWG 24 - 10  
Sez. con puntale / Max flexible with ferrule mm<sup>2</sup> 4  
DIN 46228/4 L = 8 mm

7 lb/in - 0,6 Nm

6 mm  
50

**43553**  
**43553 BL**

Diode / Diode

Grigio / Grey  
Blu / Blue  
1N4007 1A 1000V

Codice / Code Pz. conf. / Qty.p.pck.

43442	50	
43444	50	
43447	50	
43096	50	
43084	50	Protezione / Cover

43520/02	1 = 100	2 Poli / Poles
43520/03	1 = 100	3 Poli / Poles
43520/24	1 = 5	24 Poli / Poles
43516	1	

43926 R	10	
43926 S	10	
43927/01	10	

43192 - plotter	1=500	5x12 mm
43196 - plotter	1=500	6x12 mm
43060 - plotter	1=100	5x3 mm
438MFC0612ST - Script@MI	1=975	6x12 mm
438MFC0612TB - Script@MI	1=780	6x12 mm
438MFK0512TBA	1=250	5x12 mm

Accessori / Accessories: pag. 127

75 (L) x 56 (H) x 6 (B)  
4 mm<sup>2</sup> - 1000V - 32A

UL 600V 30A SEV 800V 32A  
CSA 600V 30A RINA 800V 32A  
VDE 1000V 32A Kema Ex II 2 GD EEx e II 03ATEX2118 U  
EN 60068-2-11 Test di nebbia salina per 96 ore / Salt mist test for 96 hours  
Conduttori rigidi / Rigid conductors mm<sup>2</sup> 0,5 - 6  
Conduttori flessibili / Flexible conductors mm<sup>2</sup> 0,5 - 4  
AWG 24 - 10  
Sez. con puntale / Max flexible with ferrule mm<sup>2</sup> 4  
DIN 46228/4 L = 8 mm

7 lb/in - 0,6 Nm

6 mm  
50

**43554**

Diode / Diode

Grigio / Grey  
1N4007 1A 1000V

Codice / Code Pz. conf. / Qty.p.pck.

43442	50	
43444	50	
43447	50	
43096	50	
43084	50	Protezione / Cover

43520/02	1 = 100	2 Poli / Poles
43520/03	1 = 100	3 Poli / Poles
43520/24	1 = 5	24 Poli / Poles
43516	1	

43926 R	10	
43926 S	10	
43927/01	10	

43192 - plotter	1=500	5x12 mm
43196 - plotter	1=500	6x12 mm
43060 - plotter	1=100	5x3 mm
438MFC0612ST - Script@MI	1=975	6x12 mm
438MFC0612TB - Script@MI	1=780	6x12 mm
438MFK0512TBA	1=250	5x12 mm

Accessori / Accessories: pag. 127