



NX5.08

2.30

12.60

26.00

13.70

3.30

Standard	UL	VDE
Rated voltage	300V	320V
Rated current	15A	20A
Wire range	28-12AWG	2.5mm ²
Withstanding voltage	AC2500V/1Min	
Ambient temperature	(-)40°C to +105°C	
Strip length	7mm	
Torque	0.4Nm(3.5Lb-In.)	
Pitch	5.00/5.08/7.50/7.62 mm (.197")	
Poles	2P, 3P --- Any Poles	
Housing	PA66, UL94V-0	
Screws	M2.5,steel,Cr ³ + Zn plated	
Contact	Brass, Ni plated	
Wire Cage	Brass, Ni plated	



<p>RoHS Compliant</p> <p>SCHMID-M</p>		<p>TOLERANCE</p> <p>XX ± 0.25</p> <p>XX ± 0.35</p> <p>ANG. ±</p>		<p>PART NAME</p> <p>Pluggable Terminal Block With Fix Screws</p> <p>Pitch 5,08 mm Green XX: No. Poles</p>	
<p>APPD.</p> <p>DWG. HELGA</p> <p>DATE 2013/10</p>	<p>SCAL F</p> <p>UNIT M M</p> <p>PAGE 1 OF 1</p>	<p>SIZE A 4</p> <p>REV. C</p>	<p>PART NO. SM C09 0585 XX YSC</p>		