

We are connecting the world....


C07 0109 - 2,54mm Single Row

SM C07 0109 XX Black

Standard height insulator H=7

SM C07 0109 XX H=Y

Customer height insulator H (for example 9mm) Y:3 - 9





C07 0109 D - 2,54 Dual Rows

SM C07 0109 XX D

Standard height insulator H:7

SM C07 0109 XX D H=Y

Customer height insulator Y:9




C07 0109 R - 2,54 Single Right Angle

SM C07 0109 XX R

Standard height insulator H:7

SM C07 0109 XX R H=Y

Customer height insulator H=Y




C07 0109RD - 2,54 Dual Right Angle

SM C07 0109 XX RD

Standard height insulator H:7

SM C07 0109 XX RD H=Y

Customer height insulator Y:3 - 9




C07 0109 P-15mm - 2,54 SIP Socket Machined Pin

SM C07 0109 XX P=15

Standard height insulator H:7


Pin length P=15 mm



SM C07 0109 XX D P=15

Standard height insulator H:7


Pin length P=15 mm



C07 0109 - 2,54 SMT Socket Machined Pin



SM C07 0109 XX SMT

Standard height insulator H:7



SM C07 0109 XX SMT D

Standard height insulator H:7






We are connecting the world....


C07 0112 - 2,54mm Insulator 4,2mm

C07 0113 - 2,54mm SIP Straight Socket



SM C07 0112 XX Y

XX - CONTACT No.:
01-40; 02-80
Y: BODY TYPE:
S: Single Row Straight
D: Dual Rows Straight
R: Single Row Right Angle
SMT: Single Row, SMT




SM C07 0113 XX Y

XX - CONTACT No.:
01-40; 02-80
Y: BODY TYPE:
S: Single Row Straight
D: Dual Rows Straight


C07 0116 - 2,00 SIP Socket

C07 0209 - 2,00mm SIP Socket



SM C07 0116 XX Y

XX - CONTACT No.:
01-40; 02-80
Y: BODY TYPE:
S: Single Row Straight
D: Dual Rows Straight




SM C07 0209 XX Y

XX - CONTACT No.:
01-40; 02-80
Y: BODY TYPE:
Black: Single Row Straight
D: Dual Rows Straight
R: Single Row Right Angle
RD: Dual Row; Right Angle
SMT: Single Row, SMT
SMT D: Dual Rows; SMT

C07 4881 - 2,54 Socket - Straight

C07 0170 - Battery Holder



SM C07 4881 XX Y

XX - CONTACT No.: 6-48
Y - ROW SPACING:
S: 7,62mm
H: 10,16mm
L: 15,24mm



SM C07 0170 02 Y


Y - BODY OPTION:
B: BH4 Type;
E: BH321-1A; F: BH322-1A;
H: BH331A; I: CR2032;
K: B66; L: SMD for Cr2032;
M: BH341-1P24; N: CR1220;
P: CR123A; R: BH363B;
S: BH 7 Type; U: CR2450

C07 8XXXX - Pogo Pin

SM C07 8XXYYY Z



XX - Dimension D (For Example 3,8mm = 38)
YYY - Dimension A (For Example 15mm = 150)
Z - BODY OPTION: SMT; S: Straight; D: Double Haed;
R: Right Angle; SC: Solder Cup; T: Thread



ABC Elektronik Sp. z o.o.
ul. Kolejowa 10, 38-300 Gorlice
tel.: +48 18 353-66-65
info@abcpol.pl
www.abcpol.pl



SCHMID-MULTITECH, s.r.o.
Podjavorinskej 5, 911 05 Trenčín
tel.: +421-32-7 440 186
mkovacik@smsk.sk
www.schmid-multitech.sk



ANGIELA ELEKTRONIK SRL
Str. Slanic Nr. 1 Cluj-Napoca
tel.: +42-264-403-284
info@angielia-elektronik.ro
www.angielia-elektronik.ro