

Electrolytic Capacitors - BKMJ

Characteristics

It uses dry and oil-free design, which is suitable for occasion with high requirements for security and high-end switch cabinet.

Specification of Main Products

| Type | Rated Voltage (kV) | Rated Output (kvar) | Rated Capacitance (μF) | Rated Current (A) | Length L1(mm) | Bore Distance L2(mm) | |
|-----------------|--------------------|---------------------|-------------------------------|-------------------|---------------|----------------------|-----|
| BKMJ0.44-5-1 | 0.44 | 5 | 82 | 11.4 | | | |
| BKMJ0.44-6.67-1 | | 6.67 | 110 | 15.2 | | | |
| BKMJ0.48-8.33-1 | 0.48 | 8.33 | 115 | 17.4 | | | |
| BKMJ0.4-15-3 | 400 | 15 | 299 | 21.7 | 103 | 133 | |
| BKMJ0.4-20-3 | | 20 | 398 | 28.9 | 177 | 204 | |
| BKMJ0.4-25-3 | | 25 | 498 | 36.1 | 177 | 204 | |
| BKMJ0.4-30-3 | | 30 | 597 | 43.3 | 177 | 204 | |
| BKMJ0.4-40-3 | | 40 | 796 | 57.7 | 251 | 278 | |
| BKMJ0.4-45-3 | | 45 | 896 | 65.0 | 251 | 278 | |
| BKMJ0.4-50-3 | | 50 | 995 | 72.2 | 325 | 352 | |
| BKMJ0.4-60-3 | | 60 | 1194 | 86.6 | 325 | 352 | |
| BKMJ0.44-15-3 | | 440 | 15 | 247 | 19.7 | 103 | 133 |
| BKMJ0.44-20-3 | | | 20 | 329 | 26.2 | 103 | 133 |
| BKMJ0.44-25-3 | 25 | | 411 | 32.8 | 177 | 204 | |
| BKMJ0.44-30-3 | 30 | | 493 | 39.4 | 177 | 204 | |
| BKMJ0.44-40-3 | 40 | | 658 | 52.5 | 251 | 278 | |
| BKMJ0.44-50-3 | 50 | | 822 | 65.6 | 251 | 278 | |
| BKMJ0.44-60-3 | 480 | 60 | 987 | 78.7 | 325 | 352 | |
| BKMJ0.48-30-3 | | 30 | 415 | 36.1 | 177 | 204 | |
| BKMJ0.48-40-3 | | 40 | 553 | 48.1 | 251 | 278 | |
| BKMJ0.48-50-3 | | 50 | 691 | 60.1 | 251 | 278 | |
| BKMJ0.48-60-3 | | 60 | 829 | 72.2 | 325 | 352 | |
| BKMJ0.48-70-3 | | 70 | 968 | 84.2 | 325 | 352 | |

