



We are connecting the world....

### Connector C10 SVC

SM C10 SVC 0501



Plug, Type A, Assembly

SM C10 SVC 0502



Plug, Type A, LED

SM C10 SVC 0503



Base, Type A, Circular

SM C10 SVC 0504



Plug, Type A, Assembly

SM C10 SVC 0505



Plug, Type A, LED

SM C10 SVC 0506



Base, Type A, Circular

SM C10 SVC 0507



Base, Type A, Rect.

SM C10 SVC 0511



Plug, Type B, Assembly

SM C10 SVC 0512



Plug, Type B, Assembly

SM C10 SVC 0515



Plug, Type B, Molded

SM C10 SVC 0517



Base, Type B, Rect.

SM C10 SVC 0521



Plug, Type C, Assembly

SM C10 SVC 0522



Plug, Type C, Assembly

SM C10 SVC 0525



Plug, Type C, Molded

SM C10 SVC 0527



Base, Type C

#### Type A

Standard: DIN EN 175 301-803-A  
 Ambient Temperature:  $-30^{\circ} + 125^{\circ}$   
 Pin Dimensions: 6.3x0.8mm, 4.8x0.8mm  
 Rated Voltage: 250V  
 Rated Impulse voltage: 4000V  
 Rated Current: 10A  
 IP Rating: IP 65 in locked condition  
 Cable Gland: PG9 | PG11

#### Type B

Ambient Temperature:  $-30^{\circ} + 125^{\circ}$   
 Pin Dimensions: 6.3x0.8mm, 4.8x0.8mm  
 Rated Voltage: 250V  
 Rated Impulse voltage: 4000V  
 Rated Current: 10A  
 IP Rating: IP 65 in locked condition  
 Cable Gland: PG9

#### Type C

Ambient Temperature:  $-30^{\circ} + 125^{\circ}$   
 Pin Dimensions: 4.6x0.5mm, 3.8x0.5mm  
 Rated Voltage: 250V  
 Rated Impulse voltage: 800V  
 Rated Current: 6A  
 IP Rating: IP 65 in locked condition  
 Cable Gland: PG7

