



Contacts	2+PE
Pin layout(Female)	

Notes:

Standard:Industrial Standard

Ambient Temperature:

Flexible Installation:-25°C ~ +85°C

Fixed Installation:-40°C ~ +85°C

Termination:Soldering

Pin Dimensions:6.3x0.8mm, 4.8x0.8mm

Connector Overmold:TPU

Contact Bearer Material:PA+GF

Housing Material:PC

Contact:PS with Silver Plated

Screw:Steel With Zn Plated

Seal:FKM

Gasket:TPU/NBR

Rated Voltage:24V/250V

Rated Impulse Voltage:800V/4000V

Rated Current:8A/10A

Insulation Resistance:≥100MΩ

Contact Resistance:≤4mΩ

IP Rating:IP67 In Locked Condition

Cable Type:PVC Or PUR Cable

Conductor Size:1.5mm<sup>2</sup> Max

### SM C10 SVC 0515 xxxx PG9 A LzM

xxxx - Contacts  
z - Cable Length: 1m, 3m, 5m

TOLERANCE		
SCALE	UNIT mm	
DRAW Walter	DATE 1.8.2023	TITLE
CHECK Vanda	REV	<b>SM C10 SVC 0515 xxxx PG9 B LzM</b>
		DESCRIPTION
		Solenoid Valve, Valve Plug, Type B, Female Field Wirable Molded, PG9