

ALARMS SIRENS

<https://www.atd-elektronik.cz/>
<https://www.atd-shop.com/>

SAP Series

SAS Series

SMAC Series


SXL Series

SDS Series




KEY QUESTIONS FOR ALARM DETERMINATION


1. Mounting method:
e.g. Vertical, horizontal ?



2. Connection method: wires, pins, fast-on terminals ?




3. Maximum dimensions (in mm):
length, width, depth ?




4. Supply voltage: 6, 12 or 24 Vdc ?




5. SPL – dB(A) @ 12Vdc,
@ 30 cm or 1 meter ?




6. Operating frequency range ?



7. Current consumption in mA ?



8. Temperature range in °C ?



<https://www.atd-elektronik.cz/>
<https://www.atd-shop.com/>

GENERAL OVERVIEW ALARMS & SIRENS

| Model | Function | Operating voltage | | Frequency (Hz) (±30%) | Operating current (mA) | Sound pressure level* (dB(A)) | Weight (g) |
|-------|----------|-------------------|---------|--------------------------|------------------------|----------------------------------|------------|
| | | min Vdc | max Vdc | | | | |


SAP series



| | | | | | | | |
|------------|--------------|----|----|------|-----|-----|-----|
| SAP-1302-A | intermittent | 12 | 24 | 1600 | 70 | 112 | 230 |
| SAP-1302-B | intermittent | 12 | 24 | 1600 | 65 | 107 | 230 |
| SAP-1302-C | intermittent | 12 | 48 | 1250 | 145 | 97 | 210 |
| SAP-1302-D | intermittent | 12 | 12 | 2500 | 15 | 87 | 230 |

measurement @12-24V @ 1.2 m

SAS series



| | | | | | | | |
|------------|------------|---|----|-----------|-----|-----|----|
| SAS-2155-S | sweep | 6 | 15 | 2000-3500 | 120 | 110 | 67 |
| SAST-2155 | Transducer | - | - | 2000-3500 | - | - | 67 |

measurement @12V @ 1 m


SMAC(I) series



| | | | | | | | |
|----------|--------------|---|----|-----------|-----|------|-----|
| SMAC-25 | continuous | 5 | 16 | 3350 | 9.7 | 93.5 | 7.8 |
| SMACI-25 | intermittent | 5 | 16 | 3350 | 9.7 | 93.5 | 7.8 |
| SMAC-25L | continuous | 5 | 35 | 3350 | 17 | 100 | 8.5 |
| SMACT-25 | Transducer | - | - | 3000-4000 | - | - | 7.8 |

measurement @12V @ 30 cm

SXL series



| | | | | | | | |
|-------------|---------------|---|----|------|-----|-----|----|
| SXLC 515 C | continuous | 5 | 15 | 3000 | 130 | 102 | 22 |
| SXLI 515 C1 | multifunction | 5 | 15 | 3000 | 70 | 96 | 22 |
| SXLW 515 C | warbler | 5 | 15 | 3000 | 120 | 104 | 22 |
| SXLP 515 C | sweep | 5 | 15 | 3000 | 110 | 102 | 22 |

measurement @12V @ 1 m

Sonitron Automotive Piezo components


SAP-1302 series *Back up alarm*

The 1302 series of piezo alarms generate an acoustic intermittent loud tone and are installed at the back of a car, truck, tractor, jeep, golf-trolley, ... or any other vehicle that can move in reverse at any moment, thus alerting people that are approaching the vehicle.

The 1302 series are tested for use in all weather conditions and have a lifetime in continuous use of more than **1000 hours**, this unique patented technology is used now for more than 20 years in the most extreme conditions and critical applications. (Nato, Airbus, Volvo, avionics, Bombardier railways, VDO, etc...)

A very low current consumption permits the electrical connection of the alarm to the reversing lights of the vehicle.

Installation of the reverse drive piezo alarm is realised in only one hour by anybody and does not require special skills. Adapted mounting for models on request.




Automotive Design

**ADVANTAGES & APPLICATIONS****ADVANTAGES :**

- Very low current consumption
- Dust tight, shock and water resistant (IP67)
- Low frequency (large travelling distance of audible wavelength)
- No magnetic field (EMC)
- Robust fibre reinforced PBT housing
- High lifetime in continuous function
- Easy mountable design
- Multi voltage application (12/24/48Vdc)

APPLICATIONS :

- Van
- Fork-lift
- Lorry
- Bus
- Light commercial vehicle
- Car
- Light truck
- Garbage truck
- Electric vehicles (golf, airport, warehouse, ...)
- Military vehicles




SPECIFICATIONS



| MODELS | SAP-1302-A | SAP-1302-B | SAP-1302-C | SAP-1302-D |
|--------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|---------------------------------------------------|---------------------------------------------------|
| Operating voltage: | 12/24 Vdc | 12/24 Vdc | 12/24/48 Vdc | 12 Vdc** |
| Frequency (+/-15%): | 1600 Hz (1Hz intermittent) | 1600 Hz (1Hz intermittent) | 1250 Hz (1Hz intermittent) | 2500 Hz (1Hz intermittent) |
| Current consumption: | 12Vdc: 145 mA (avg.) 24Vdc: 70 mA (avg.) | 12Vdc: 140 mA (avg.) 24Vdc: 65 mA (avg.) | 145 mA (avg.) | 15 mA (avg.) |
| SPL@1.2m: | 112 dBA (+/- 4 dB) | 107 dBA (+/- 4 dB) | 97 dBA (+/- 4 dB) | 87 dBA (+/- 4 dB) |
| Life time (@21°C): | >1000 hours*** | >1000 hours*** | >1000 hours*** | >1000 hours*** |
| Case material: | PBT (UL rating: 94HB) | PBT (UL rating: 94HB) | PBT (UL rating: 94HB) | PBT (UL rating: 94HB) |
| Standard color of case: | Black | Black | Black | Black |
| Terminal material: | (F2)Fast-on or 30cm cable 2x1.5mm ² | (F2)Fast-on or 30cm cable 2x1.5mm ² | (F2)Fast-on or 30cm cable 2x1.5mm ² | (F2)Fast-on or 30cm cable 2x1.5mm ² |
| Storage Temp. range: | -40°C/+85°C | -40°C/+85°C | -40°C/+85°C | -40°C/+85°C |
| Operating Temp. range: | -40°C/+85°C | -40°C/+85°C | -40°C/+85°C | -40°C/+85°C |
| Weight: | 230 g | 230 g | 210 g | 230 g |

- **Output voltage depending: min. 5 Vdc=76 dBA, max. 16Vdc=91 dBA.
- ***Lifetime: more than 1000 hours in continuous use,
(Voltage: 12 Vdc ; T ambient: 21°C ; Humidity: 40 % ; Free air).


"Models on request" can be designed for this alarm construction!
 Same housing other alarm tone: - pulse tone
 - continuous tone
 - sweep tone, ...
 Contact Support@sonitron.be




<https://www.atd-elektronik.cz/>
<https://www.atd-shop.com/>

Sound pressure level vs. operating voltage


SAP-1302-A




SAP-1302-B



SAP-1302-C



SAP-1302-D



All measurements are made @ 12Vdc @1.2 meter in free air @ 21°C.


LIST OF AVAILABLE PRODUCT TYPES

| | |
|---------------|------------------------------|
| SAP-1302-A-F2 | (Fast-on F2, tinned brass) |
| SAP-1302-A-W | (standard cable lenght=30cm) |
| SAP-1302-B-F2 | (Fast-on F2, tinned brass) |
| SAP-1302-B-W | (standard cable lenght=30cm) |
| SAP-1302-C-F2 | (Fast-on F2, tinned brass) |
| SAP-1302-C-W | (standard cable lenght=30cm) |
| SAP-1302-D-F2 | (Fast-on F2, tinned brass) |
| SAP-1302-D-W | (standard cable lenght=30cm) |




<https://www.atd-elektronik.cz/>
<https://www.atd-shop.com/>

Dimensions (in mm)




SAP-1302-A-B-C
Fast-on position

Cable version
Standard cable length: 30 cm





SAP-1302-D
Fast-on position


Cable version
Standard cable length: 30 cm



Mounting guidelines



2x M6 screw, nut and washer recommended for mounting



Packaging

One piece per box.

