




Spacer support, round spacer, threaded spacer




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 3-11 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- h.:11.1+8.7 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 2-27mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 3.2-38.1 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- height: 2-22 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 9.2-38.1 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 3.2-25.4 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 2.0-9.0 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 2.0-7.5 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height:5-26 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- height: 2-27mm




- screw terminal
- Flame class: 94V-2
- Color: Natural
- height:11.9,19.4,9mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- screws, equipments




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- PCB Hinge, Bracket




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- threaded spacers




- screw terminal
- Flame class: 94V-2
- Color: Natural, Gray
- silicon spacers




- Mat.:Nylon 66/6T,PC
- Flame class: 94V-2
- Color: Natural, Black
- support,spacer supp.



- Body Material: ABS
- Nut Material: Iron
- Color: Natural
- spacer support




- Material: Nylon 66,PC
- Flame class: 94V-2, 0
- Color: Natural, Black
- spacer support



- Material: Nylon 66,PC
- Flame class: 94V-2
- Color: Natural
- support,spacer supp.

90° LED spacer support




- Material: Nylon 66
- Flame class: 94V-2,0
- Color: Natural, Black
- height: 1.5-24.0 mm



- Material: Nylon 66
- Flame class: 94V-2,0
- Color: Natural, Black
- height: 3-12 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- LED holders




- Material: Nylon 66, PC
- Flame class: 94V-2
- Color: Natural, Black
- height: 10.3, 7.1 mm




- Material: Nylon 66
- Flame class: 94V-2
- Color: Black
- height: 6.3-7.1 mm




- Material: Nylon 66, PC
- Flame class: 94V-2
- Color: Natural, Black
- Lens cap, LED holder




- Material: PC, PMMA
- Flame class: 94V-2
- Color: Natural, Clear
- Light pipe




- Material: PC
- Flame class: 94V-2
- Color: Natural, Clear
- Lens cap, Light pipe




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- height: 5-27 mm



- Material: Nylon 66, PC
- Flame class: 94V-2
- Color: White, Black
- LED holder cover



- Material: Nylon 66
- Flame class: 94V-2
- Color: Black
- height: 11.4-13.2 mm




- Material: PC
- Flame class: 94V-2
- Color: Clear
- Light pipe


90° LED spacer support, LED holder, LED mask




- Material: PC
- Flame class: 94V-2,0
- Color: Natural
- Light pipe, supp.




- Material: PC, PMMA
- Flame class: 94V-2,0
- Color: Natural, Clear
- Light pipe



- Material: Nylon 66, PC
- Flame class: 94V-2
- Color: Natural, Black
- Lens cap




- Material: Nylon 66
- Flame class: 94V-2,0
- Color: Black
- height: 12-20.4 mm




- Material: Nylon 66
- Flame class: 94V-2,0
- Color: Black
- LED spacer support



- Material: Nylon 66
- Flame cl.: 94 HB, V-2
- Color: Natural, Black
- Photo TR holder




- Material: Nylon 66
- Flame class: 94V-2
- Color: Black
- LED spacer support




- Material: Nylon 66
- Flame class: 94V-2
- Color: Black
- height: 16.6 mm


Mount / Lock / Stisk Wire Mark, F. B. T. Clip




- Mat.: Nylon 66, PVC
- Flame class: 94V-2
- Color: Natural, Gray
- Flat cable mount




- Material: Nylon 66
- Flame class: 94V-2,0
- Color: Natural
- Flat cable clamp




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- Wire mount




- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black
- Wire mount



- Mat.: Nylon 66, PPO
- Flame class: 94V-2
- Color: Natural, Black
- Wire mount



- Material: Nylon 66
- Flame class: 94V-2
- Color: Gray
- Flat cable clamp



- Material: Nylon 66
- Flame class: 94V-2
- Color: White, Gray
- Wire mount



- Material: Tinplate, Steel, Nylon 66
- Flame class: 94V-2
- Wire mount



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- length: 64.2-117 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: White, Black
- length: 86.75 mm



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- Wire holder



- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural
- Fiber cable housing

Hole plugs, Strain relief bushing, Movable bushing, Box handle




- Snap bushing
- Material: Nylon 66
- Color: Black
- Ø 8-38 mm



- Snap bushing
- Material: Nylon 66
- Color: Black, White
- Ø 23.3, 25 mm




- Hole plugs
- Flame class: 94V-2
- Color: Natural, Black
- Ø 6.35-34.2 mm



- Switch Power bushing
- Strain Relief bushing
- Color: Black
- Ø 15.9, 11.2 mm



- Anti vibrate grommet
- Material: TPE
- Color: Black, Blue...
- Ø 2.7 × 5 mm



- Cable ties
- Material: Nylon 66
- Flame class: 94V-2
- Color: Natural, Black



- Strap ties
- Material: Nylon 66
- Flame class: 94V-2
- Color: Black, White



- Heat-shrinkable tubing
- Mat.: Polyolefin
- Ø 1-50 mm

Connector, Terminal block, Wire clamp, P.C.B. Terminal, Fuse holder




- Test pins
- Mat.: Tin plated copper
- Length: 7-18 mm



- Test pins
- Material: Tin plated brass
- Length: 6-17 mm




- Fuse holders
- Mat.: Phospor bronze C2680, Tin plated, Brass, Nylon




- PCB Terminals
- Rated: 15 A
- Size: 11.1×9.2 mm, 8×8 mm




- PCB Terminals
- Rated: 15 A
- Material: Tin plated brass



- PCB Terminals
- Material: Tin plated brass, Plated nickel brass



- PCB Terminals
- Material: Tin plated brass
- Mount. hole: 5 mm




- PCB Terminals
- Material: Tin plated brass
- Mounting hole: 5 mm




- PCB Terminals
- Material: Tin plated brass
- Ø 4.3 - 5.3 mm



- Ground terminals
- Material: Tin plated brass
- Ø 4.5 mm




- TR clamp
- Material: SUS301
- Height: 6.4, 7.2, 7.5, 3.7mm




- Plastic gear
- Gear mat.: POM 94HB
- Body mat.: ABS 94HB
- Øpitch:6.6,8.8,10.4mm

Card guide



- Card pullers
- Mat.: Nylon 66, POM
- Color: Natural, White
- Length:28,28.2,31.2



- Card pullers
- Mat.: Nylon 66, POM
- Color: Natural, Black
- Length:31.2,38,38.26



- Card guide
- Flame class: 94V-2,0
- Color: Natural, Black
- Mount. holes: 101.6



- Card guide
- Flame class: 94V-2,0
- Color: Natural, Red
- Material: Nylon 66



- Card guide
- Flame class: 94V-2
- Color: Natural, Black
- Material: Nylon 66



- Card guide
- Material: Nylon 66
- Flame class:94V-2
- Color: Natural, Black



- Card guide
- Material: Nylon 66
- Flame class:94V-2
- Color: Natural, Black



- Card guide
- Material: Nylon 66
- Flame class:94HB,V-2
- Color: Natural, Black