

Comercial SPDT Switch DC-18GHZ Failsafe Type



RF SPEC.:

Frequency Range	DC-3GHZ	3-6GHZ	6-12.4GHZ	12.4-18GHZ
VSWR	<1.20	<1.30	<1.40	<1.50
Insertion Loss	<0.2dB	<0.3dB	<0.4dB	<0.5dB
Isolation	>80dB	>70dB	>60dB	>60dB
Power Handling(CW)	100W	70W	50W	40W

- . RF Impedance: 50 ohm
- . Operating Voltage: DC12V/200mA
(Option:DC24V/100mA,DC28V/110mA)
- . Switching Time: <15ms
- . Life:>2000000cycles
- . Switching Sequence:Break Before Make
- . Operating Temperature: -55 ~ +85°C
- . RF Interface: SMA female

P/N: 1S2

1 2 DC12V 0 3 DC-3GHZ NO TTL

2 4 DC24V 0 6 DC-6GHZ T TTL

2 8 DC28V 1 2 DC-12GHZ

1 8 DC-18GHZ

sample: **1S2 12 18** :SMA SPDT/DC12V/DC-18GHZ/NO TTL Control

TTL LOGIC	C-NC	C-NO
Logic "0" (0-0.8V)	Connection	Broken
Logic "1" (2.5-5V)	Broken	Connection

SIZE:

