

**Comercial SPDT Switch DC-18GHZ**

**Latching Type**

**RF SPEC.:**

Frequency Range	DC-3GHZ	3-6GHZ	6-12.4GHZ	12.4-18GHZ
VSWR	<1.20	<1.30	<1.40	<1.50
Insertion Loss	<0.2dB	<0.3dB	<0.4dB	<0.5dB
Isolation	>80dB	>70dB	>60dB	>60dB
Power Handling(CW)	85W	50W	30W	20W



- . RF Impedance: 50 ohm
- . Operating Voltage: DC12V/220mA ;DC24V/85mA; DC28V/100mA
- . Switching Time: <15ms
- . Life:>1000000cycles
- . Switching Sequence:Break Before Make
- . Operating Temperature: -40 ~ +65°C
- . RF Interface: SMA female

P/N: L1S2

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
<input type="checkbox"/> 1	<input type="checkbox"/> 2	DC12V	<input type="checkbox"/> 0	<input type="checkbox"/> 3	DC-3GHZ
<input type="checkbox"/> 2	<input type="checkbox"/> 4	DC24V	<input type="checkbox"/> 0	<input type="checkbox"/> 6	DC-6GHZ
<input type="checkbox"/> 2	<input type="checkbox"/> 8	DC28V	<input type="checkbox"/> 1	<input type="checkbox"/> 2	DC-12GHZ
			<input type="checkbox"/> 1	<input type="checkbox"/> 8	DC-18GHZ

**Size:**

