

AS -

ASU -

Series AS(U)- 85°C 15000h


Capacitors screw terminal type

- AS - Flat Bottom
- ASU - Mounting Stud
- Capacitance Tolerance: -20 + 20% - standard (M)
- Capacitance Tolerance: -10 + 30% - on request (X)
- Self extinguishing construction and electrolyte
- Climatic category: 40/85/56
- Case: 51x105 - 90x222
- Temperature - 40°C + 85°C
- All welded construction reliable electrical contact

Mechanical Outlines

- Case: aluminium made
- Terminals: screw
- Sealing: hermetic by EPR gasket, on a resin cover
- Pressure Release Vent: silicone-rubber
- Sleeve: self-extinguishing thermo shrinkable
- Size: see enclosed drawings
- Mounting Hardware: see hardware section
- External Material UL94-V0

Ordering Code: Example



Ripple Current

The allowable values of ripple current in Ampères, are related to the temperature and frequency by following equation:

$$I_{\text{Ripple}} = K_t \cdot K_f \cdot I_{\text{Ripple}@85^\circ\text{C}}$$

Where:

- $I_{\text{Ripple}@85^\circ\text{C}}$ is the limit given by tables, @ 85°C/100HZ
- K_t is the Temperature Correlation Factor
- K_f is the Frequency Correlation Factor

Note .Superimposed alternating voltage summed to DC volage must not exceed rated voltage, rated ripple current must not be exceeded and no reverse polarity is allowed

°C	40	55	65	75	85
K_t	2.10	1.80	1.60	1.30	1.00

Table 1-Kt Values

V_n/Hz	K_f			
	$50 < V = 300$		$V > 300$	
	Diameter Code A,B		Diameter Code C,D,E	
50	0.79	0.76	0.78	0.72
100	1.00	1.00	1.00	1.00
120	1.04	1.04	1.02	1.03
200	1.12	1.17	1.06	1.14
300	1.16	1.28	1.08	1.24
400	1.20	1.35	1.09	1.29
500	1.22	1.39	1.09	1.32
>1000	1.25	1.45	1.09	1.37

Table 2-Kf Values

Expected Lifetime End of Life Criteria

During useful life typical electrical parameters of electrolytic capacitor are subject to change.

End of Life criteria, when rated temperature, voltage and ripple are applied, are:

$$\frac{\Delta C}{C_{t0}} \leq 30\% \quad \text{Equation 1}$$

$$ESR \leq 3 \cdot ESR_{t0} \quad \text{Equation 2}$$

$$I_r \leq I_{rt0} \quad \text{Equation 3}$$

where t_0 is the initial value

Voltage Endurance Test Requirements

Voltage Endurance Test are one of the basys for Expected Lifetime Curves.

End of Life criteria, when rated temperature, and voltage are applied for 2'000hrs, are

$$\frac{\Delta C}{C_{t0}} \leq 10\% \quad \text{Equation 4}$$

$$ESR \leq 1,3 \cdot ESR_{t0} \quad \text{Equation 5}$$

$$I_r \leq I_{rt0} \quad \text{Equation 6}$$

where t_0 is the initial value

Expected Lifetime Vs Temperature and Ripple Current




Table 3

Leakage Current

After the rated voltage has been applied to the capacitor for 5 minutes the leakage current must be within those limits.

Maximum limit	@25°C	$I_f \leq 1.5 \cdot \sqrt{C \cdot V}$
Operating limit	@25°C	$I_f \leq 1.5 \cdot \sqrt{C \cdot V}$

Where: I_f =leakage current [μ A], C =capacitance [μ F], V =rated voltage [V]


Surge Voltage

Working Voltage	100	160	200	250	350	400	450	500
Surge Voltage	130	215	250	300	425	475	525	550

	Capacitance	Case	Diam	Height	Tanδ	ESRmax typ		Zmax	Iripple @100Hz		Ordering Code
	[μF]@100Hz		[mm]	[mm]	[%]@100Hz	[mΩ]@100Hz	[mΩ]@10KHz	[mΩ]@10KHz	[A]@55°C	[A]@85°C	(U) for mounting stud
100	4700	BC	51	105	0,12	41	33	29	17,0	9,5	AS(U)M472M100BC1
	6800	BC	51	105	0,12	28	22	21	21,0	11,4	AS(U)M682M100BC1
	10000	CC	63	107	0,12	19	15	14	28,0	15,6	AS(U)M103M100CC1
	15000	DC	76	107	0,13	14	11	11	37,0	20,4	AS(U)M153M100DC1
	22000	DF	76	147	0,13	9	8	9	51,0	28,3	AS(U)M223M100DF1
	33000	DF	76	147	0,13	6	5	5	61,0	33,9	AS(U)M333M100DF1
160	2200	BC	51	105	0,10	72	58	50	13,0	7,1	AS(U)M222M160BC1
	3300	CC	63	107	0,10	48	39	34	18,0	9,8	AS(U)M332M160CC1
	4700	DC	76	107	0,12	41	33	31	21,0	11,9	AS(U)M472M160DC1
	6800	DF	76	147	0,12	28	22	21	29,0	16,4	AS(U)M682M160DF1
	10000	DF	76	147	0,12	19	15	14	36,0	19,9	AS(U)M103M160DF1
	15000	DF	76	147	0,12	13	10	12	40,5	22,4	AS(U)M153M160DF1
200	1500	BC	51	105	0,08	85	68	59	12,0	6,6	AS(U)M152M200BC1
	2200	CC	63	107	0,08	58	46	41	16,0	9,0	AS(U)M222M200CC1
	3300	CC	63	107	0,09	43	35	32	19,0	10,4	AS(U)M332M200CC1
	4700	DC	76	107	0,10	34	27	25	23,0	13,1	AS(U)M472M200DC1
	10000	DF	76	147	0,11	18	14	13	36,5	20,3	AS(U)M103M200DF1
250	1500	BC	51	105	0,08	85	68	64	11,4	6,4	AS(U)M152M250BC1
	2200	CC	63	107	0,09	65	52	49	14,8	8,2	AS(U)M222M250CC1
	3300	DC	76	107	0,10	48	39	36	19,2	10,7	AS(U)M332M250DC1
	4700	DF	76	147	0,10	34	27	25	26,3	14,6	AS(U)M472M250DF1
	6800	DF	76	147	0,10	23	19	18	31,6	17,6	AS(U)M682M250DF1
	10000	DJ	76	222	0,10	16	13	12	46,2	25,6	AS(U)M103M250DJ1
	15000	DJ	76	222	0,10	11	8	8	56,5	31,4	AS(U)M153X250DJ1
350	680	BC	51	105	0,07	164	131	124	8,0	4,4	AS(U)M681M350BC1
	1000	BC	51	105	0,07	108	87	85	10,0	5,4	AS(U)M102M350BC1
	1500	CC	63	107	0,08	81	65	66	13,0	7,0	AS(U)M152M350CC1
	2200	DC	76	107	0,09	62	50	51	16,0	8,9	AS(U)M222M350DC1
	3300	DF	76	147	0,09	41	33	35	22,0	12,5	AS(U)M332M350DF1
	4700	DF	76	147	0,07	24	19	24	27,0	14,9	AS(U)M472M350DF1
	6800	DJ	76	222	0,10	23	19	20	39,0	21,7	AS(U)M682M350DJ1
400	680	BC	51	105	0,10	234	187	151	7,0	4,0	AS(U)M681M400BC1
	1000	CC	63	107	0,10	159	127	105	10,0	5,4	AS(U)M102M400CC1
	1500	DC	76	107	0,10	106	85	72	13,0	7,4	AS(U)M152M400DC1
	2200	DC	76	107	0,11	80	64	51	15,0	8,5	AS(U)M222M400DC1
	2200	DF	76	147	0,10	72	58	51	18,0	10,2	AS(U)M222M400DF1
	3300	DF	76	147	0,12	58	46	35	21,0	11,4	AS(U)M332M400DF1
	4700	DF	76	147	0,12	41	33	35	24,8	13,5	AS(U)M472M400DF1
	6800	DJ	76	222	0,12	28	22	26	30,0	16,4	AS(U)M682M400DJ1
450	1500	CC	63	107	0,10	106	80	60	9,5	6,8	AS(U)M152M450CC1
	2200	CC	63	107	0,12	87	65	49	10,5	7,5	AS(U)M222M450CC1
	3300	DC	76	107	0,12	58	43	36	14,3	10,2	AS(U)M332M450DC1



	Capacitance	Case	Diam	Height	Tanδ	ESRmax typ		Zmax	Iripple @100Hz		Ordering Code
	[μF]@100Hz		[mm]	[mm]	[%]@100Hz	[mΩ]@100Hz	[mΩ]@10KHz	[A]@55°C	[A]@85°C	(U) for mounting stud	
450	3300	DF	76	147	0,10	48	36	28	17,9	12,8	AS(U)M332M450DF1
	4700	DF	76	147	0,12	41	30	24	19,5	13,9	AS(U)M472M450DF1
		EC	90	107	0,12	41	30	25	21,8	15,6	AS(U)M472M450EC1
	5600	DF	76	147	0,12	34	27	29	30,0	16,4	AS(U)M562M450DF1
		DJ	76	222	0,13	37	30	28	31,0	17,2	AS(U)M562M450DJ1
	6800	DJ	76	222	0,12	28	21	17	28,3	20,2	AS(U)M682M450DJ1
		EF	90	147	0,12	28	21	17	26,2	18,7	AS(U)M682M450EF1
	10000	DJ	76	222	0,12	19	14	20	32,5	22,8	AS(U)M103M450DJ1
EJ		90	222	0,12	19	14	12	37,7	26,9	AS(U)M103M450EJ1	
500	470	BB	51	83	0,10	339	271	254	5,2	2,9	AS(U)M471M450BB1
		BC	51	106	0,10	339	271	254	5,8	3,2	AS(U)M471M450BC1
	1000	BC	51	105	0,10	159	127	98	8,0	4,2	AS(U)M102M500BC1
	1500	DC	76	107	0,10	106	85	74	11,0	6,0	AS(U)M152M500DC1
	2200	DC	76	107	0,10	72	58	54	13,4	7,6	AS(U)M222M500DC1
		DF	76	147	0,10	72	58	47	15,0	8,3	AS(U)M222M500DF1
	3300	DF	76	147	0,10	48	39	27	16,0	9,1	AS(U)M332M500DF1
	3900	DF	76	147	0,10	41	32	22	18,3	11,2	AS(U)M392M500DF1
	4400	DF	76	147	0,10	35	28	2	23,7	13,5	AS(U)M442M500DF1
	4700	DF	76	147	0,08	27	22	18	27,0	15,4	AS(U)M472M500DF1
		EF	90	147	0,08	27	22	18	30,1	17,2	AS(U)M472M500EF1
	5600	EF	90	147	0,12	34	27	26	34,1	18,9	AS(U)M562M450EF1
	6800	EF	90	147	0,12	28	22	21	37,5	20,8	AS(U)M682M450EF1
	10000	EJ	90	220	0,12	19	15	14	54,4	30,2	AS(U)M103M450EJ1

Dimension, Quantity and Weight for box


Case				Connections							Mounting Stud			Packaging	
Code	DxL	L1	h1	d1	d2	e	Terminal	Screw			Screw			Pcs/Box	Weight/box
							Code	Thread	Torque	Lenght	d3	c	Torque		
BC	51x105	109	13	13	18	22.2	M	M5	2,0	10	M12	16	10Nm	30	6-9
CC	63x107	111	16	13	18	28.6	M	M5	2,0	10	M12	16	10Nm	20	6-8
DC	76x107	111	19	13	18	31.8	M	M5	2,0	10	M12	16	10Nm	12	5-7
DF	76x147	151	19	13	18	31.8	M	M5	2,0	10	M12	16	10Nm	12	6-14
				17	23		G	M6	2,5						
DK	76x167	173	19	13	18	31.8	M	M5	2,0	10	M12	16	10Nm	12	6-14
				17	23		G	M6	2,5						
DJ	76x220	222	19	13	18	31.8	M	M5	2,0	10	M12	16	10Nm	8	9-11
				17	23		G	M6	2,5						
EC	90x107	112	19	17	23	31,8	G	M6	2,5	10	M12	16	10Nm	6	7-9
EF	90x147	153	19	17	23	31,8	G	M6	2,5	10	M12	16	10Nm	6	9-11
EJ	90x220	227	19	17	23	31,8	G	M6	2,5	10	M12	16	10Nm	6	8-12

All dimensions in mm, torque in Nm, weight in kg