







# STANDARD SERIES

## CHOGORI

### Standard Series Specifications

#### Standard Series, Panel Mount & Male Pin

Description	Panel Front Mount, Screw Type, PCB	Panel Front Mount, Lock Bayonet Type, PCB	Panel Front Mount, Push Lock Type, PCB
Figure			

Drawing			
---------	---	--	---

Part Number	Contacts	Part Number	Contacts	Part Number	Contacts	Part Number
	2	22002515-02	2	22002525-02	2	22002535-02
	3	22003515-02	3	22003525-02	3	22003535-02
	4	22004515-02	4	22004525-02	4	22004535-02
	5	22005515-02	5	22005525-02	5	22005535-02
	6	22006515-02	6	22006525-02	6	22006535-02
	2+4	22204515-02	2+4	22204525-02	2+4	22204535-02
	3+4	22304515-02	3+4	22304525-02	3+4	22304535-02
	8	22008515-02	8	22008525-02	8	22008535-02
	10	22010515-02	10	22010525-02	10	22010535-02
	12	22012515-02	12	22012525-02	12	22012535-02

#### Specifications

Number of Contacts	2	3	4	5	6	2+4	3+4	8	10	12
Wire Gauge	0.823mm <sup>2</sup> (18AWG)			0.519mm <sup>2</sup> (20AWG)		0.823mm <sup>2</sup> (18AWG)*2C/3C 0.519mm <sup>2</sup> (20AWG)*4C		0.519mm <sup>2</sup> (20AWG)	0.34mm <sup>2</sup> (22AWG)	
Panel Thickness	Max. 4.0mm				Max. 4.0mm			Max. 3.0mm		
Environmental Protection	IP68				IP67			IP67		
Mechanical Life	500 mating cycles									
Operating Temperature	- 45°C - 105°C									
Voltage Rating	300V	300V	125V	60V	60V	60V	60V	60V	30V	30V
Rated Current (40°C)	10A	10A	10A	5A	5A	10A+5A	10A+2A	5A	2A	2A

COMPANY PROFILE  
500 Series  
Mini Series  
Standard Series  
Middle Series  
Large Series  
Distributor Series  
RJ45 Series  
USB Series  
D-Sub series  
T-Adapter Series  
Splitter Series  
HDMI Series  
M8/M12 CONN Series  
M Series Distributor