



|                      |                    |                     |
|----------------------|--------------------|---------------------|
| Standard             | UL                 | IEC                 |
| Rated voltage        | 600V               | 400V                |
| Rated current        | 10A                | 18A                 |
| Wire range           | 18-16AWG           | 1.50mm <sup>2</sup> |
| Withstanding voltage | AC2500V/1Min       |                     |
| Ambient temperature  | -40°C~+105°C       |                     |
| Strip length         | 10--13mm           |                     |
| Pitch                | 3.00mm(.100")      |                     |
| Poles                | 3P / 5P /8P        |                     |
| Housing              | PA66+5%GF.,UL94V-0 |                     |
| Pin header           | Brass,Ni plated    |                     |
| Wire guard           | Stainless steel    |                     |



RoHS  
Compliant

**SCHMID-M**

|            |           |                         |  |
|------------|-----------|-------------------------|--|
| APPD.      | <br>SCALE | TOLERANCE               | <b>PART NAME</b><br>Terminal Block, Spring Style,<br>Pitch 3,00mm, Wire to Wire,<br>XX..... Nr. Pins |
| DWG.       |           | .0 ±<br>.00 ±<br>ANG. ± |  |
| DATE       | UNIT      | SIZE.                   | <b>PART NO.</b><br>SM C09 33018 XX WC1   |
| 2014/01/28 | M M       | A 4                     |  |
|            | PAGE      | REV.                    |  |
|            | 1 OF 1    | A                       |  |