





m12 Receptacle

M12 (Metal Die-Casting) Receptacle, Female, A, B & D-Coding

Description	Receptacle, Front Fastened, Screw Type, Solder
Figure	

Drawing	
---------	--

Coding	A-Coding (X=1)	B-Coding (X=2)	D-Coding (X=4)
			

Part No.	Contacts		Part Number		Contacts		Part Number	
	A, B, D-Coding	3	M16X1.5	54036X05-07	4	M16X1.5	54046X05-07	PG9
PG9			54036X05-17	PG9		54046X05-17		
A-Coding	5	M16X1.5	54056X05-07	12	M16X1.5	54126105-07	PG9	54126105-17
		PG9	54056X05-17		PG9	54126105-17		

Specifications					
Number of Contacts	3	4	5	8	12
Voltage Rating	250V	250V	60V	30V	30V
Rated Current (40°C)	4A	4A	4A	2A	1.5A
Max Panel Thickness	4.5mm (max)				
Environmental Protection	IP68				
Mechanical Life	100 mating cycles (min)				
Operating Temperature	-40°C - 85°C				

Conductor Type					
Wire Gauge	0.34mm ² (22AWG)	0.34mm ² (22AWG)	0.34mm ² (22AWG)	0.25mm ² (24AWG)	0.14mm ² (26AWG)