

● General Specifications

- ⌚ Material ----- Frame:Aluminum
Impeller:Plastics (Flammability:UL94V-0 rating)
- ⌚ Dielectric Strength ----- 50/60Hz 1500VAC 1minute
- ⌚ Life time -----15000 Hours Sleeve bearing
30000 Hours Ball bearing
- ⌚ Storage Temperatur--- -30°C ~ +70°C (Non-condensing)
- ⌚ Bearing Type----- Ball Bearings Sleeve
- ⌚ Speed Range----- ±10%
- ⌚ Part Numbering System
SFD-AC15050H 220 B - 1
Waterproof level:1=IP55,2=IP68
Bearing:S=sleeve bearing,B=ball bearing
AC Voltage: 110=100-125V、220=220-240V



135 X 135 X 38mm (Mass510g)

Model No.	Voltage (v)	Frequ ency	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure	Noise
	VAC	HZ	A/MP	Watt	R.P.M	M3/min	CFM	IN H2O	dB-A
FAN-AC13538M110B	100~125	50/60	0.19/0.25	13/18	2700/3000	2.49/2.92	88/102	0.23/0.28	42/46
FAN-AC13538H220B	220~240	HZ	0.11/0.12	13/16	2700/3000	2.49/2.92	88/102	0.23/0.28	42/46

● Dimensions(unit:mm/inch)

● Air Flow-Static Pressure Characteristics

